

ELECTRIC PRESSURE WASHER

N-SERIES

Standard configuration

- Copper Cylinder Ceramic Plunger Crankshaft Connecting Rod Self-Priming Pump
- Powerful power with overload protection 4-stage motor
- Motor aluminum alloy shell 8mmx10M high pressure tube
- 4 quick connect nozzles (0°, 15°, 25°, 40°)
- The pressure is adjustable
- High-pressure spray gun with safety buckle
- Water hose and spray gun hook
- Water inlet pipes and their components
- Switch control box
- Stainless steel chassis
- Pressure gauge



Matching

- Voltage and power can be specified
- Turn off the gun and shut it down



Technical parameters

Model	Working Pressure		Flow Rate	Power		Voltage	Speed	G.W.	Carton Size
	Bar	PSI	L/MIN	KW	HP	V	RPM	KG	MM
NCB-1410	100	1450	14	2.2	3.0	220	1450	60	720X390X550
NBC-1412	120	1750	14	2.5	3.3	220	1450	65	720X390X550
NBC-1413	130	1885	14	3.0	4.0	220	1450	68	720X390X550
NCB-1415	150	2175	14	3.0	4.0	380	1450	63	720X390X550
NBC-1520	200	2900	15	4.0	5.5	380	1450	69	720X390X550
NAB-1522	220	3200	15	5.5	7.5	380	1450	88	860X440X550
NAB-1525	250	3625	15	7.5	10.0	380	1450	96	860X440X550
NAA-1530	300	4350	15	10.0	14.0	380	1450	108	860X440X550